



Technical Informations



Certificazione di qualità
UNI EN ISO 9001:2008

Classic line

Code	040-0000000001
Name	Dismounted locker
Dimensions (WxDxH)	420x500x1800 mm
Inside Dimensions (WxDxH)	418x480x1610 mm
N° places	1
N° places for column	1
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	29
Volume (m3)	0,11



General informations

Base and corpus	BASE ELEMENT.	Base
	on low socle. Corpus made by modular interlocking panels with front frames support. Sides with 30 mm. frontal thickness with cut proof edges and bent on tree levels.	
Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.	
Lock	Cylinder lock type Yale with double key.	
Closing	One way lever	
Inside	Upper steel shelf at h.402 mm. From the roof with clothes hanger bar and 2 "S"galvanized hooks.	
Colour door	Painting with epoxy powder color RAL 7035.	
Colour corpus	Painting with epoxy powder color RAL 7035.	
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.	

Possibilities

Door	Without ventilation, with holes type 1
Lock	padlock handle,embedded padlock,mechanic combination ,electronic combination
Closing	3 point, upper, lower and in the middle.
Inside	Upper shelf with division wall and lower shelf,only upper shelf,empty.

Colour door

RAL-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 purc orange	RAL-3001 sigeal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6016 Yellow green

Colour corpus



Technical Informations

SINCERT



UNI EN ISO 14001/2004



Certificazione di qualità
UNI EN ISO 9001:2008

Code **040-0000000001**

Accessories.

Sloping roof

Mirror

Adjustable feet

Padlock

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

Certifications

UNI 8596:2005 Stability

UNI 8597:2005 Structure resistance

UNI 8603:2005 Shelves supports resistance

UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Cargo total maximum

UNI 8600:2005 Bending with concentrated cargo

UNI 8601:1984 Bending of shelves

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03