

Technical Informations





Linea Classica

Codice articolo 053-0000000001

Denominazione Monobloc locker

Dimensioni (LxPxH) 1020x500x1800 mm

Dimensioni vano (LxPxH) 358x480x1610 mm

N° posti/vani 3

N° posti/vani 3 N° vani per colonna 1

Materiale DC01/FeP01 UNI EN 10130

Peso (Kg) 50 Volume (m3) 0,92







General informations

Base and corpus

Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet.

Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between

roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels

Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side

and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed

label holder.

Lock Cylinder lock type Yale with double key.

Closing One way lever

inside Upper shelf h.247 mm.from the roof with bar and 2 S galvanized hooks. Division wall. Steel towel

/Umbrella holderon the door. Plastic tray for drops.

Colour door Painting with epoxy powder color RAL 7035.
Colour corpus Painting with epoxy powder color RAL 7035.

Law In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and

finishing.

Possibilities

Base On base, on inox feet, without feet.

Door Without ventilation, with holes type 1, grid, HPL or plexiglass.

Lock padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock

(€.1,00).

Closing 3 point, upper, lower and in the middle.

Inside Upper shelf with division wall and lower shelf, upper shelf and division wall, upper am lower

shelf, without shelves .

Colour door

Rul-7035 SiAL-8015 Sight trony signal pure orange signal red raby red sky blue water blee light blue green grigio Steece Blue

Colour corpus



Technical Informations





Certificazione di qualità UNI EN ISO 9001:2008

Code **053-0000000001**

Accessories.

Sloping roof

Support bench

Mirror

2 sides for base

Frontal base

Kit "S" Hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

Certifications

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance tosudden changes in temparature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test-Pencil method

UNI EN ISO 2409/2007 Grid test