



# Technical Informations

SINCERT



Certificazione di qualità  
UNI EN ISO 9001:2008

## Classic line

|                            |                         |
|----------------------------|-------------------------|
| Code                       | <b>101-0000000001</b>   |
| Name                       | Welded locker           |
| Dimensions (WxDxH )        | 322x500x1800 mm         |
| Inside Dimensions (WxDxH ) | 320x480x1610 mm         |
| N° places                  | 1                       |
| N° places for column       | 1                       |
| Material                   | DC01/FeP01 UNI EN 10130 |
| Weight (Kg)                | 19,5                    |
| Volume (m3)                | 0,29                    |




### General informations

|                 |   |
|-----------------|---|
| Base and corpus | Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels |
| Door            | Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.   |
| Lock            | Cylinder lock type Yale with double key.  |
| Closing         | One way lever   |
| Inside          | Upper shelf h.247 mm.from the roof with bar and 2 S galvanized hooks. Steel towel /Umbrella holder on the door. Plastic tray for drops.   |
| Colour door     | Painting with epoxy powder color RAL 7035.  |
| Colour corpus   | Painting with epoxy powder color RAL 7035.  |
| Law             | In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.  |

### Possibilities

|         |   |
|---------|---|
| Base    | On base,on inox feet, without feet.   |
| Door    | Without ventilation, with holes type 1, grid, HPL or plexiglass.  |
| Lock    | padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock (€1,00).             |
| Closing | 3 point, upper, lower and in the middle.  |
| Inside  | Upper shelf with division wall and lower shelf, upper shelf and division wall,with upper and lower shelf,empty. |

### Colour door



### Colour corpus



## Technical Informations

SINCERT



Certificazione di qualità  
UNI EN ISO 9001:2008

Code **101-0000000001**

### Accessories.

Sloping roof

Support bench

Mirror

2 sides for base

Frontal base

Kit "S" Hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

### Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

### Certifications

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

**These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet**

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03