



# Technical sheet



Certificato Sistema di Gestione Qualità n° 50.100.2898

Reg. n° 8231-E ISO 14001

## Classic Line

Code	<b>1706-0000000001</b>
Description	Monobloc compartments locker
Dimensions (WxDxH)	615x500x1800 mm
Inner dimensions (WxDxH)	320x480x525 mm
Entrance dimensions (WxH)	232x474 mm
Places Nr.	6
Places each column	3
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	36
Volume (m3)	0,55



### General characteristics

Base and body	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended panel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels.
Doors	Doors fitted with internal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.
Lock	Cylinder lock type Yale with double key.
Closing	One way lever.
Inside	Empty
Door colour	Painting with epoxy powder color RAL 7035.
Body colour	Painting with epoxy powder color RAL 7035.
Reference normatives	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

### Options

Base	On base, on inox feet, without feet.
Doors	Without ventilation, with holes type 1, grid, HPL or plexiglass.
Lock	Padlock handle, embedded padlock, mechanic combination ,electronic combination and coin lock (€1,00).
Closing	One way lever.
Inside	Empty

### Colours with extra fee

Door colours

RAL 1003	RAL1003	RAL7035	RAL1003
RAL 1015	RAL1015	RAL7035	RAL1015
RAL2004	RAL2004	RAL7035	RAL2004
RAL3001	RAL3001	RAL7035	RAL3001
RAL3003	RAL3003	RAL7035	RAL3003
RAL5012	RAL5012	RAL7035	RAL5012
RAL5015	RAL5015	RAL7035	RAL5015
RAL5010	RAL5010	RAL7035	RAL5010
RAL6018	RAL6018	RAL7035	RAL6018



# Technical sheet



Certificato Sistema di  
Gestione Qualità  
n° 50 100 2898



Reg. n° 8231-E  
ISO 14001

Disegnato e sviluppato da: P. BERTONDA  
Ingegneri, accreditati da: ACCREDIA

Code **1706-0000000001**

## Accessories

- Sloping roof
- Support bench
- 2 sides for base
- Frontal base
- Adjustable feet
- Padlock
- Anti-corrosion cover for feet

## Spare parts

- Cylinder lock type Yale with double key
- Padlock handle
- Door H. mm. 330

## Certifications

- UNI 9115/87 Taber erosion
- UNI 9428/89 Resistance to scratches
- UNI 9429/89 Resistance to sudden changes in temperature
- UNI 9300/88 and FA 276/89 Tendency to get dirty
- UNI 9427/89 Resistance to light
- UNI 9149/89 Mirror-like reflection
- UNI EN ISO 9227/2006 Resistance to corrosion
- UNI 8901/86 Resistance to slamming
- UNI EN ISO 1520/95 Resistance trials
- UNI 10782/1999 Hardness test- pencil method
- UNI EN ISO 2409/2007 Grid test

**La presente scheda è proprietà esclusiva di San Polo Lamiere S.p.A. Div. Armet**

Riproduzione vietata ai sensi di legge (art.171 Legge 22/04/1941 ,n.633).

L'utilizzo fraudolento ,senza regolare autorizzazione scritta anche se parziale e con qualsiasi mezzo, sarà tutelato a norma di Legge.

Il testo e quanto sopra specificato contengono informazioni riservate al destinatario indicato.

Il contenuto della presente e-mail confidenziale e la sua riservatezza è tutelata legalmente dal D.L.196/03.