



Technical sheet



Certificato Sistema di Gestione Qualità n° 50 100 2898

Reg. n° 8231-E ISO 14001

Classic Line

Code	1712-0000000001
Description	Monobloc compartments locker
Dimensions (WxDxH)	1200x500x1800 mm
Inner dimensions (WxDxH)	320x480x525 mm
Entrance dimensions (WxH)	232x474 mm
Places Nr.	12
Places each column	4
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	74
Volume (m3)	1,08



General characteristics

Base and body	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended panel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels.
Doors	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.
Lock	Cylinder lock type Yale with double key.
Closing	One way lever.
Inside	Empty
Door colour	Painting with epoxy powder color RAL 7035.
Body colour	Painting with epoxy powder color RAL 7035.
Reference normatives	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Options

Base	On base, on inox feet, without feet.
Doors	Without ventilation, with holes type 1, grid, HPL or plexiglass.
Lock	Padlock handle, embedded padlock, mechanic combination ,electronic combination and coin lock (€1,00).
Closing	One way lever.
Inside	Empty

Colours with extra fee

Door colours

RAL 1003	RAL 1003	RAL 7035	RAL 1003
RAL 1015	RAL 1015	RAL 7035	RAL 1015
RAL 2004	RAL 2004	RAL 7035	RAL 2004
RAL 3001	RAL 3001	RAL 7035	RAL 3001
RAL 3003	RAL 3003	RAL 7035	RAL 3003
RAL 5012	RAL 5012	RAL 7035	RAL 5012
RAL 5015	RAL 5015	RAL 7035	RAL 5015
RAL 5010	RAL 5010	RAL 7035	RAL 5010
RAL 6018	RAL 6018	RAL 7035	RAL 6018



Technical sheet



Certificato Sistema di
Gestione Qualità
n° 50 100 2896



Reg. n° 8231-E
ISO 14001

Code **1712-0000000001**

Accessories

Sloping roof
Support bench
2 sides for base
Frontal base
Adjustable feet
Padlock
Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key
Padlock handle
Door H. mm. 330

Certifications

UNI 9115/87 Taber erosion
UNI 9428/89 Resistance to scratches
UNI 9429/89 Resistance to sudden changes in temperature
UNI 9300/88 and FA 276/89 Tendency to get dirty
UNI 9427/89 Resistance to light
UNI 9149/89 Mirror-like reflection
UNI EN ISO 9227/2006 Resistance to corrosion
UNI 8901/86 Resistance to slamming
UNI EN ISO 1520/95 Resistance trials
UNI 10782/1999 Hardness test- pencil method
UNI EN ISO 2409/2007 Grid test

La presente scheda è proprietà esclusiva di San Polo Lamiere S.p.A. Div. Armet

Riproduzione vietata ai sensi di legge (art.171 Legge 22/04/1941 ,n.633).

L'utilizzo fraudolento ,senza regolare autorizzazione scritta anche se parziale e con qualsiasi mezzo, sarà tutelato a norma di Legge.

Il testo e quanto sopra specificato contengono informazioni riservate al destinatario indicato.

Il contenuto della presente e-mail confidenziale e la sua riservatezza è tutelata legalmente dal D.L.196/03.