



Technical sheet



Certificato Sistema di Gestione Qualità n° 50.100.2898

Reg. n° 8231-E ISO 14001

Classic Line

| | |
|--------------------------|-------------------------|
| Code | 203-0000000001 |
| Description | Monobloc locker |
| Dimensions (WxDxH) | 1200x500x1800 mm |
| Inner dimensions (WxDxH) | 418x480x1610 mm |
| Places Nr. | 3 |
| Places each column | 1 |
| Material | DC01/FeP01 UNI EN 10130 |
| Weight (Kg) | 62 |
| Volume (m3) | 1,08 |



General characteristics

| | |
|----------------------|--|
| Base and body | Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels. |
| Doors | Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder. |
| Lock | Cylinder lock type Yale with double key. |
| Closing | One way lever |
| Inside | Upper shelf h.247 mm.from the roof with bar and 2 S galvanized hooks. Division wall between shelf and bottom. Steel towel /Umbrella holder on the door. Plastic tray for drops. |
| Door colour | Painting with epoxy powder color RAL 7035. |
| Body colour | Painting with epoxy powder color RAL 7035. |
| Reference normatives | In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing. |

Options

| | |
|---------|--|
| Base | On base,on inox feet, without feet. |
| Doors | Without ventilation, with holes type 1, grid, HPL or plexiglass. |
| Lock | padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock (€.1,00). |
| Closing | 3 point, upper, lower and in the middle. |
| Inside | Upper shelf with division wall and lower shelf,only upper shelf,empty. |

Colours with extra fee

Door colours

| | | | |
|----------|----------|----------|----------|
| RAL 1003 | RAL 1003 | RAL 7035 | RAL 1003 |
| RAL 1015 | RAL 1015 | RAL 7035 | RAL 1015 |
| RAL 2004 | RAL 2004 | RAL 7035 | RAL 2004 |
| RAL 3001 | RAL 3001 | RAL 7035 | RAL 3001 |
| RAL 3003 | RAL 3003 | RAL 7035 | RAL 3003 |
| RAL 5012 | RAL 5012 | RAL 7035 | RAL 5012 |
| RAL 5015 | RAL 5015 | RAL 7035 | RAL 5015 |
| RAL 5010 | RAL 5010 | RAL 7035 | RAL 5010 |
| RAL 6018 | RAL 6018 | RAL 7035 | RAL 6018 |



Technical sheet



Certificato Sistema di
Gestione Qualità
n° 50 100 2898



Reg. n° 8231-E
ISO 14001

Code **203-0000000001**

Accessories

Sloping roof

Support bench

Mirror

2 sides for base

Frontal base

"S" -hooks kit

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

Certifications

UNI 8596:2005 Stability

UNI 8597:2005 Structure resistance

UNI 8603:2005 Shelves supports resistance

UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Cargo total maximum

UNI 8600:2005 Bending with concentrated cargo

UNI 8601:1984 Bending of shelves

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

La presente scheda è proprietà esclusiva di San Polo Lamiere S.p.A. Div. Armet

Riproduzione vietata ai sensi di legge (art.171 Legge 22/04/1941 ,n.633).

L'utilizzo fraudolento ,senza regolare autorizzazione scritta anche se parziale e con qualsiasi mezzo, sarà tutelato a norma di Legge.

Il testo e quanto sopra specificato contengono informazioni riservate al destinatario indicato.

Il contenuto della presente e-mail confidenziale e la sua riservatezza è tutelata legalmente dal D.L.196/03.