



Technical informations



Certificato Sistema di Gestione Qualità n° 50 100 2898

Reg. n° 8231-E ISO 14001

Quadro Line

Code	244-0000000001
Name	Multi compartment locker
Dimensions (WxDxH)	810x500x1800 mm
Inside Dimensions (WxDxH)	418x480x805 mm
Entrance dimensions	330x775 mm
N° places	4
N° places for column	2
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	45
Volume (m3)	0,72



General Informations

Base and corpus	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts,predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended panel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels
Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, squared holes for ventilation ,squared handle with label holder.
Lock	Cylinder lock typo Yale with double key.
Closing	One way lever
Inside	Steel clothes hanging bar with plastic supports and hooks in every door.
Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Possibilities

Base	On base, inox feet, without feet.
door	Without ventilation, with grid, HPL or plexiglass.
lock	padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock (€1,00).
closing	One way lever
Inside	Shelf, empty

door color



corpus color





Technical informations



Code **242-0000000001**

Accessories.

- Sloping roof
- Support bench
- 2 sides for base
- Frontal base
- Adjustable feet
- Padlock
- Anti-corrosion cover for feet

Spare parts

- Cylinder lock type Yale with double key
- Padlock handle
- Door H. mm. 395

Certifications

- UNI 8596:2005 Stability
- UNI 8597:2005 Structure resistance
- UNI 8603:2005 Shelves supports resistance
- UNI 9081:2005 Resistance of the doors to vertical cargo
- UNI 8606:2005 Cargo total maximum
- UNI 8600:2005 Bending with concentrated cargo
- UNI 8601:1984 Bending of shelves
- UNI 9115/87 Erosion Taber
- UNI 9428/89 Resistance to scratches
- UNI 9429/89 Resistance to sudden changes in temperature
- UNI 9300/88 e FA 276/89 Tendency to get dirty
- UNI 9427/89 Resistance to light
- UNI 9149/89 Mirror-like reflection
- UNI EN ISO 9227/2006 Resistance to corrosion
- UNI 8901/86 Resistance to slamming
- UNI EN ISO 1520/95 Resistance trials
- UNI 10782/1999 Hardness test- Pencil method
- UNI EN ISO 2409/2007 Grid test

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03