



Technical sheet



Certificato Sistema di
Gestione Qualità
n° 50 100 2898

Reg. n° 8231-E
ISO 14001

"Combi" Quadro Line

Code	248-0000000001	
Description	Monobloc locker	
Dimensions (WxDxH)	1200x500x1800 mm	
Inner dimensions (WxDxH)	415x480x805 mm -	415x480x398 mm
Places Nr.	8	
Places each column	2x2 + 1x4	
Material	DC01/FeP01 UNI EN 10130	
Weight (Kg)	62	
Volume (m3)	0,81	



General characteristics

Base and body	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels.
Doors	"Quadro" -perforated doors ,fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.
Lock	Cylinder lock type Yale with double key.
Closing	One way lever.
Inside	Compartment lockers: empty ; Multi compartments : coat hanger bar with galvanised-steel "S" hooks
Door colour	Painting with epoxy powder color RAL 7035.
Body colour	Painting with epoxy powder color RAL 7035.
Reference normatives	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Options

Base	On base,on inox feet, without feet.
Doors	Without ventilation, with holes type 1, grid, HPL or plexiglass.
Lock	Padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock (€1,00).
Lock	
Closing	Lower shelf

Colours with extra fee

Door colours

RAL 1003	RAL1003	RAL7035	RAL1003
RAL 1015	RAL1015	RAL7035	RAL1015
RAL2004	RAL2004	RAL7035	RAL2004
RAL3001	RAL3001	RAL7035	RAL3001
RAL3003	RAL3003	RAL7035	RAL3003
RAL5012	RAL5012	RAL7035	RAL5012
RAL5015	RAL5015	RAL7035	RAL5015
RAL5010	RAL5010	RAL7035	RAL5010
RAL6018	RAL6018	RAL7035	RAL6018



Technical sheet



Certificato Sistema di
Gestione Qualità
n° 50 100 2898



Reg. n° 8231-E
ISO 14001

Code **248-0000000001**

Accessories

Sloping roof

Support bench

Mirror

2 sides for base

Frontal base

Kit "S" Hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 330

Certifications

UNI 8596:2005 Stability

UNI 8597:2005 Structure resistance

UNI 8603:2005 Shelves support resistance

UNI 8602:2005 Opening and closing with door slamming

UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Maximum total cargo

UNI 8600:2005 Bending with concentrated cargo

UNI 9115/87 Taber erosion

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 and FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

La presente scheda è proprietà esclusiva di San Polo Lamiere S.p.A. Div. Armet

Riproduzione vietata ai sensi di legge (art.171 Legge 22/04/1941 ,n.633).

L'utilizzo fraudolento ,senza regolare autorizzazione scritta anche se parziale e con qualsiasi mezzo, sarà tutelato a norma di Legge.

Il testo e quanto sopra specificato contengono informazioni riservate al destinatario indicato.

Il contenuto della presente e-mail confidenziale e la sua riservatezza è tutelata legalmente dal D.L.196/03.