



Technical informations



Certificato Sistema di Gestione Qualità
n° 50 100 2898

Reg. n° 8231-E
ISO 14001

Linea Quadro

Code	252-0000000001
Name	2 DOORS LOCKER
Dimensions (WxDxH)	810x500x1800 mm
Inside Dimensions (WxDxH)	418x480x1610 mm
N° places	2
N° places for column	1
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	49
Volume (m3)	0,72



General Informations

Base and corpus	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels
Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, squared holes for ventilation ,squared handle with label holder.
Lock	Cylinder lock typo Yale with double key.
Closing	One way lever
Inside	Upper shelf at h.247 mm.from the roof with clothes hanger bar with hooks .
Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Possibilities

Base	On base, inox feet, without feet.
door	Without ventilation, with grid, HPL or plexiglass.
lock	padlock handle, embedded padlock, mechanic combination ,electronic combination and coin lock (€1,00).
closing	3 points , high low and in the middle.
Inside	Upper shelf with separation and lower shelf, upper shelf with separation, without shelves and separation.

door color

RAL-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow green

corpus color



Technical informations



Certificato Sistema di
Gestione Qualità
n° 50 100 2898



Reg. n° 8231-E
ISO 14001

Code **252-0000000001**

Accessories.

Sloping roof

Support bench

Mirror

2 sides for base

Frontal base

Kit "S" hooks

Kit adjustable feet

Padlock for padlock handle

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

Certifications

UNI 8596:2005 Stability

UNI 8597:2005 Structure resistance

UNI 8603:2005 Shelves supports resistance

UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Cargo total maximum

UNI 8600:2005 Bending with concentrated cargo

UNI 8601:1984 Bending of shelves

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03