

Technical informations





Certificato Sistema di Gestione Qualità Reg. n° 8231-E ISO 14001

Linea Quadro

 Code
 253-0000000001

 Name
 3 DOORS LOCKER

 Dimensions (WxDxH)
 1200x500x1800 mm

 Inside Dimensions (WxDxH 418x480x1610 mm

N° places 3 N° places for column 1

Material DC01/FeP01 UNI EN 10130

Weight (Kg) 62 Volume (m3) 1,08









General Informations

Base and corpus

Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels

Door Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side

and anticut bend on tree orders on the remaining sides, squared holes for ventilation, squared

handle with label holder.

Lock Cylinder lock typo Yale with double key.

Closing One way lever

Inside Upper shelf at h.247 mm.from the roof with clothes hanger bar with hooks .

Colour door Painting with epoxy powder color RAL 7035.
Colour corpus Painting with epoxy powder color RAL 7035.

Law In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and

finishing.

Possibilities

Base On base, inox feet, without feet.

door Without ventilation, with grid, HPL or plexiglass.

lock padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock

(€.1,00).

closing 3 points, high low and in the middle.

Inside Upper shelf with separation and lower shelf, upper shelf with separation, without shelves and

separation.

door color

corpus color

Ral-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow green
Ral-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow green

S. POLO LAMIERE S.p.A. divisione ARMET Via Cisa Ligure,43-42041 BRESCELLO (RE) ITALIA Tel.+39.0522.686009—Fax+39.0522.686015-info@armet.it-www.armet.it



Technical informations





Certificato Sistema di Gestione Qualità nº 50 100 2898 Reg. n° 8231-E ISO 14001

Code **253-0000000001**

Accessories.

Sloping roof

Support bench

Mirror

2 sides for base

Frontal base

Kit "S" hooks

Kit adjustable feet

Padlock for padlock handle

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1605

Certifications

UNI 8596:2005 Stability

UNI 8597:2005 Structure resistance

UNI 8603:2005 Shelves supports resistance

UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Cargo total maximum

UNI 8600:2005 Bending with concentrated cargo

UNI 8601:1984 Bending of shelves

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance tosudden changes in temparature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test