

Technical informations





Gestione Qualità

Reg. n° 8231-E ISO 14001

Linea Quadro

Code **273-0000000001**

Name Multi compartment locker

Dimensions (WxDxH) 420x500x1800 mm
Inside Dimensions (WxDxH) 418x480x535 mm
Entrance dimensions 330x505 mm
N° places 3
N° places for column 3

Material DC01/FeP01 UNI EN 10130

Weight (Kg) 28 Volume (m3) 0,37









General Informations

Base and corpus

Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels

Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side

and anticut bend on tree orders on the remaining sides, squared holes for ventilation, squared

handle with label holder.

Lock Cylinder lock typo Yale with double key.

Closing One way lever

Inside Steel clothes hanging bar with plastic supports and hooks in every door.

Colour door Painting with epoxy powder color RAL 7035.
Colour corpus Painting with epoxy powder color RAL 7035.

Law In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and

finishing.

Possibilities

Base On base, inox feet, without feet.

door Without ventilation, with grid, HPL or plexiglass.

lock padlock handle, embedded padlock, mechanic combination, electronic combination and coin lock

(€.1,00).

closing One way lever Inside Shelf, empty

door color

RAL-1015 RAL-1015 RAL-2004 RAL-2001 RAL-2003 RAL-2015 RAL-5015 RAL-5012 RAL-5012 Vallow green Proper orange orange orange RAL-2001 RAL-2003 RAL-5015 RAL-5012 RAL-5012 RAL-5012 RAL-5013 RAL-501



Technical informations





Certificato Sistema d Gestione Qualità n° 50 100 2898 Reg. n° 8231-ISO 14001

Code **273-0000000001**

Accessories.

Sloping roof

Support bench

2 sides for base

Frontal base

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 535

Certifications

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance tosudden changes in temparature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test