



# Technical Informations



Certificato Sistema di Gestione Qualità n° 50 100 2898



Reg. n° 8231-E ISO 14001

## Schedo Line

Code	<b>CLI02-000000001</b>
Name	Filing cabinet
Dimensions (WxDxH )	460x630x735 mm
Inside Dimensions (WxDxH)	390x540x300 mm
N° places	2
N° places for column	2
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	38
Volume (m3)	0,28



## General informations

Base and corpus	Steel base , h. 60 mm. Corpus made by pannels of thickness 8/10, sides predisposed for the drawers slides, rounded edges.
Drawers	Drawers ,made in steel sheet thickness 8/10 reinforced in the overstraining points.The drawers runs on robusts telescopic slides with total extraction, the closing is with only one lock that closes all the drawers in the same time and is equipped with an anti tipping safety device that prevent the simoulytaneous opening of several drawers; with arched handle and label holder.
Lock	cylinder lock with simultaneus closing of all the drawers with 2 keys. one way lever.
Closing	N ° 2 drawers that allows the accomodation of hanging folders with distance 39 cm, while every drawer is fitted with an additionnal trellis for those of 33 cm. In case of accomodation of cards,the maximun high is 300 mm.
Inside	
Colour drawing	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

## Possibilities

Base	-
Door	-
Lock	-
	-
Closing	Drawers can be equipped by a longitudinal partition that divides in 2 lanes of width 18,4 cm eachone and /or vertical dividers, high 320 mm, to supporta nd divide documents .
Inside	

Colour door



Colour corpus



# Technical Informations



Certificato Sistema di  
Gestione Qualità  
n° 50 100 2898

Reg. n° 8231-E  
ISO 14001

Code **CLI02-000000001**

## Accessories.

Longitudinal partition that divide the drawer in 2 lanes

Vertical partition h 320 mm

## Spare parts

Cylinder lock with simoutaneous closing of all drawers with 2 keys.

Arched handle

## Certifications

UNI 8596:2005 Stability

UNI 8597:2005 Structure resistance

UNI 8603:2005 Shelves supports resistance

UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Cargo total maximum

UNI 8600:2005 Bending with concentrated cargo

UNI 8601:1984 Bending of shelves

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance tosudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

**These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet**

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03