S. POLO LAMIERE S.p.A. divisione ARMET Via Cisa Ligure, 43-42041 BRESCELLO (RE) ITALIA Tel. +39.0522.686009–Fax+39.0522.686015-info@armet.it-

www.armet.it







Gestione Qualità nº 50 100 2898

Schedo Line

Code	S18L-000000001
Name	Knocked down Slinding doors cabinet
Dimensions (WxDxH)	1800x450x880 mm
Inside Dimensions (WxDxH	(874x2)x380x780 mm
N° places	2
N° places for column	1
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	64
Volume (m3)	0,34





General informations

Base and corpus	Steel base, h. 80 mm. Corpus made by panels thickness 8/10 fixed by screws, bottom,top, back ,sides on rack thickness 40 mm.with rounded edges.
door Lock	Sliding doors on bearings in the upper and lower part with anticut folds on 4 orders and central reinforcement. Plastic handle color black.
Closing	Button lock with double safety key. one way lever
Inside	N °1+ 1 adjustable shelves on rack, with galvanized supports.
Colour drawing	
Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.
Possibilities	
Base	-
Door	-
Lock	-

Inside

Closing

Colour door



Colour corpus



S. POLO LAMIERE S.p.A. divisione ARMET Via Cisa Ligure, 43-42041 BRESCELLO (RE) ITALIA Tel. +39.0522.686009–Fax+39.0522.686015-info@armet.it-

www.armet.it



S18L-000000001

Couple of adjustable shelves on rack, with galvanized supports.

Code

Accessories.

Melaminate Top L.1800 mm.

Technical Informations





Spare parts Button lock with double safety key. Handle for sliding doors with screws Right or left sliding door H. mm. 780 Certifications UNI 8596:2005 Stability UNI 8597:2005 Structure resistance UNI 8603:2005 Shelves supports resistance UNI 9081:2005 Resistance of the doors to vertical cargo

UNI 8606:2005 Cargo total maximum

UNI 8600:2005 Bending with concentrated cargo

UNI 8601:1984 Bending of shelves

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance tosudden changes in temparature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.