S. POLO LAMIERE S.p.A. divisione ARMET Via Cisa Ligure, 43-42041 BRESCELLO (RE) ITALIA Tel. +39.0522.686009–Fax+39.0522.686015-info@armet.it-

www.armet.it

Technical Informations





Classic line

Code	S2B-0000000001			
Name	Welded locker			
Dimensions (WxDxH)	810x330x1800 mm		6.4	and the second s
Inside Dimensions (WxDxH 418x310x1610 mm				
N° places	2			
N° places for column	1			
Material	DC01/FeP01 UNI EN 10130		•	
Weight (Kg)	47			
Volume (m3)	0,48			
	35			
General informations				

Base and corpus	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet.			
	Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between			
	roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels			

Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.				
Lock	Cylinder lock type Yale with double key.				
Closing	One way lever				
Inside	Upper shelf h.247 mm.from the roof with bar and 2 S galvanized hooks, lower shelf delimiting the space for shoes h.188 mm. from the bottom. Division wall. Steel towel /Umbrella holderon the door. Plastic tray for drops.				
Colour door	Painting with epoxy powder color RAL 7035.				
Colour corpus	Painting with epoxy powder color RAL 7035.				
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.				
Possibilities					
Base	On base,on inox feet, without feet.				
Door	Without ventilation, with holes type 1, grid, HPL or plexiglass.				
Lock	padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock (${f c}.1,00$).				
Closing	3 point, upper, lower and in the middle.				
Inside	Upper shelf with division wall and lower shelf, only upper shelf, empty.				
Colour door	Ral-7035 RAL-1015 RAL-2004 RAL-2004 RAL-3001 RAL-5015 RAL-5012 RAL-5012 RAL-5012 RAL-5013 RAL-6016 Yellow				
Colour corpus	Ral-7035 RAL-1015 RAL-1003 RAL-2004 RAL-3001 RAL-5015 RAL-5021 RAL-5022 RAL-3003 Yellow				
	ingin grey ingine rooty yellow orange signal real sky brue water brief ingine brief ruby real green. Pag.1/2				

S. POLO LAMIERE S.p.A. divisione ARMET Via Cisa Ligure,43-42041 BRESCELLO (RE) ITALIA Tel.+39.0522.686009–Fax+39.0522.686015-info@armet.it-

www.armet.it



Technical Informations





UNI EN ISO 14001/2004 Certificazione di qualità UNI EN ISO 9001:2008

Code	S2B-0000000001	UNI EN ISO 14001/2004	UNI EN ISO 9001:2008
Accessories.			
Sloping roof			
Mirror			
2 sides for base			
Frontal base			
Kit "S" Hooks			
Adjustable feet			
Padlock			
Anti-corrosion cover for	r feet		
Spare parts			
Cylinder lock type Yale w	vith double key		
Padlock handle			
Door H. mm. 1605			
Certifications			
UNI 8596:2005 Stability			
UNI 8597:2005 Structure	e resistance		
UNI 8603:2005 Shelves supports resistance			
UNI 9081:2005 Resistand	ce of the doors to vertical cargo		
UNI 8606:2005 Cargo to	tal maximum		
UNI 8600:2005 Bending	with concentrated cargo		
UNI 8601:1984 Bending	of shelves		
UNI 9115/87 Erosion Tal	ber		
UNI 9428/89 Resistance	to scratches		
UNI 9429/89 Resistance	tosudden changes in temparature		
UNI 9300/88 e FA 276/8	9 Tendency to get dirty		
UNI 9427/89 Resistance	to light		
UNI 9149/89 Mirror-like	reflection		
UNI EN ISO 9227/2006 R	Resistance to corrosion		
UNI 8901/86 Resistance	to slamming		
UNI EN ISO 1520/95 Re	esistance trials		
UNI 10782/1999 Hardne	ess test- Pencil method		
UNI EN ISO 2409/2007 (Grid test		

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).