



Technical Informations



Certificato Sistema di Gestione Qualità
n° 50 100 2898

Reg. n° 6231-E
ISO 14001

Tecno Line

Code	VFO-0000000001
Name	Monobloc locker
Dimensions (WxDxH)	600x500x1950 mm
Inside Dimensions (WxDxH)	598x480x1800 mm
N° places	1
N° places for column	1
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	32
Volume (m3)	0,58



General informations

Base and corpus	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts,predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels
Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots ,printed label holder.
Lock	Cylinder lock typo Yale with double key.
Closing	One way lever
Inside	Clothes hanging bar with 2 "S" galvanized hooks. N ° 2 adjustable shelves in 4 positions. umbrella/towel in chromed steel mounted on the door. Plastic glass drop holder, unbreakable mirror.
Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Possibilities

Base	On base,on inox feet, without feet.
Door	Without treatments, with holes type 1,with grid.
Lock	Padlock, embidded padlock handle, mechanic combination ,electronic combination and coinlock (€1,00).
Closing	3 ways, upper,lower and in the middle.
Inside	Separation with n° 3 shelves in the right side and 1 shelf in the left side boots holders,only clothes hanging bar,without shelves.

Colour door



Colour corpus





Technical Informations



Certificato Sistema di
Gestione Qualità
n° 50 100 2898



Reg. n° 8231-E
ISO 14001

Code **VFO-0000000001**

Accessories.

Kit "S" Hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 1770

Certifications

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03