



Technical Informations



Certificato Sistema di Gestione Qualità n° 50 100 2898

Reg. n° 8231-E ISO 14001

Tecno Line

Code	VFS-0000000001
Name	Monobloc locker
Dimensions (WxDxH)	600x500x800 mm
Inside Dimensions (WxDxH)	598x480x770 mm
N° places	1
N° places for column	1
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	18
Volume (m3)	0,25



General informations

Base and corpus	Without feet, steel frame, h. 30 mm. . Body made by one pannel and joint roof and back with microjoint top to back to create holes for ventilation and sides with front thickness 30 mm. with anticut edges folded on 3 levels.
Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper ventilation slots ,printed label holder.
Lock	Cylinder lock typo Yale with double key.
Closing	One way lever
Inside	N ° 2 adjustable shelves on 4 positions

Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Possibilities

Base	-
Door	Without treatments, with holes type 1,with grid.
Lock	Padlock, embidded padlock handle, mechanic combination ,electronic combination and coinlock (€1,00).
Closing	-
Inside	without shelves

Colour door										
	RAL-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow-green
Colour corpus										
	RAL-7035 light grey	RAL-3001 signal red								



Technical Informations



Certificato Sistema di
Gestione Qualità
n° 50 100 2898



Reg. n° 8231-E
ISO 14001

Code **VFO-00000000001**

Accessories.

padlock

Spare parts

Cylinder lock type Yale with double key

Padlock handle

Door H. mm. 740

Cerification

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03